

## Legend to Vehicle Reference List

Heed all Indexes! - Symbols and #'s must be followed !

- + VW / Audi quick fit belt can be installed without vehicle alteration.
- S Stock seat not approved. For installation of tail strap to this anchor point, use only special seats, tested and approved by SCHROTH.  
For SCHROTH tested and approved special seats see list below.

10) Index "S" do not refer to vehicles equipped with RECARO front seats ("sport seats").

27) To avoid release of the pyrotechnic seat pretensioning devices the battery has to be disconnected 10 minutes before starting installation.

35) If stock 3-point belt should be removed from the car never remove stock seat belt buckle as there is a safety device included (VW-description: lunar module) which never must be removed from the car.

## List of Approved Special Seats

**COBRA SUPAFORM:** Cobra S, Instyle/LS, Montreaux

**CORBEAU EQUIPE:** Avanti Recliner, GTB Recliner, GTS Recliner

**FLOFIT:** Flofit-Sport

**KEIPER RECARO:** Orthopäd (Orthopedic), Designer Touring (design touring), Idealsitz SR, L, LX, LS 84, CS 84, CSE, T-Line, Designer Sport (design sport), C-Classic, TX, N, LS, CT, Variomed, A 8

**KÖNIG:** K330/370, K430/470, K530/570, K630/670, K730/770, K830/870, KS400/4000/700, CP400/4000/700, P700, RL200, CL200/400, RS/RSL 4400/8800

Be sure to contact your local Cobra, Corbeau, Flofit, König or Recaro dealer for information regarding seats recommended for the make, model and model year of your car.

## Vehicle Reference List

### SCHROTH VW / AUDI Quick Fit Belt

Make Model	Model No.	Mod. Year	VW/ AUDI QuickFit Belt
<b>AUDI</b>			
4000	81	1980 - 1987	S
5000	43	1980 - 1983	S
5000 wagon	43	1980 - 1983	S
5000, -turbo	44	1982 - 1988	+
5000 quattro, -turbo quattro	44 Q	1984 - 1988	+
100, 200	44	1988 - 1991	+
Coupé, GT	85	1982 - 1987	S
Coupé, 4000 CS quattro, 80, 90 not Audi Quattro	89	1988 - 1989	+
V 8	D11	1988 - 1994	+
A4 <sup>27)</sup>	B5	1994 - 2001	+
A6 <sup>27)</sup>		1994 - 2002	+
<b>VOLKSWAGEN</b>			
Beetle	11	1960 - 1979	S
Rabbit	17	1975 - 1984	S
New Beetle <sup>27)</sup> , <sup>35)</sup>	1C	1998 -	+
New Beetle Cabrio <sup>27)</sup> , <sup>35)</sup>		2002 -	+
Jetta I		1980 - 1984	S
Scirocco I		1975 - 1981	S
Golf	17, 1G	1985 - 1992	+
Jetta II	16, 1G	1985 - 1992	+
Golf III, Jetta III	1H	1993 - 1999	+
Golf convertible	15	1980 - 1995	S <sup>10)</sup>
Golf IV <sup>27)</sup> , <sup>35)</sup>	9B	1998 -	+
Jetta IV <sup>27)</sup>	9M	1998 -	+
Jetta station <sup>27)</sup>	9M	1998 -	+
Dasher		1976 - 1981	S
Passat sedan, -station	31	1989 -	+
Scirocco II	53	1982 - 1988	S <sup>10)</sup>
Corrado	50	1990 - 1995	+

For indexes see Legend of Vehicle Reference List

### HMS Motorsport

3 First Avenue  
Peabody, MA 01960  
Toll Free (888) 536-8550  
Phone (978) 532-1145  
Fax (978) 532-2016

Our Service Number  
**(800) 884-BELT**  
guides you to your nearest dealer.



This belt is designed and manufactured specifically for use only in specific VW / AUDI models as listed in this vehicle reference list. Compare your car's specifications to the type no. and model year of vehicle in this vehicle reference list. Use of this belt in any other VW / AUDI model or any other make and model is strictly prohibited. Use of this belt in such vehicles can cause serious personal injuries or death in the event of an accident.

This product is not designed and tested to be used with HANS® or other head and neck restraints e.g. Hutchens device.

If stock seats with integrated side airbags or seat-based sensors are being replaced by aftermarket seats care is necessary to ensure that the entire vehicle safety systems are not compromised. Elimination of seat based airbags sensors by swapping seats could result in a faulty deployment and/or non-function of airbags and permanent illumination of dashboard airbag system warning light. Buckle-pretensioners must never be removed from the vehicle with or without the seat without being secured against unintended firing. Removing buckle-pretensioners from the car also may disturb the function of other safety devices including the front airbags. Heed all instructions and information given in the vehicle's Owner Manual. Before changing seats, check with the vehicle manufacturer to see if your factory provided seats are so equipped, and if so, what provisions and precautions are necessary to preserve factory safety systems.